
HuaYaoPV

Hyper N54

515~535W **HY535-N108EDD**

N-TOPCon, Bi-facial
108-cell, MBB
0~+3% positive tolerance



KEY FEATURES

Mbb half cell design
Half-cut cells brings lower cell connection loss and lower thermal coefficients to ensures higher power output

More Power
Industry leading N-TOPCon technology applied to generate ultra-high power up to 535Wp with optimized temperature coefficient and lower working temperature

High Reliability
Strict outsourcing BOM materials quality control and 100% in-house wafer and the TOPCon cell performance boost the power warranty to 30 Year

Excellent Low-light Performance
Advanced N-TOPCon solar cell technology allows for excellent performance in low-light environments


Highly Strengthened Design
Certified to withstand 5400Pa snow load and 2400Pa wind load

PID Resistant
Excellent PID resistance performance optimized by unique cell process design and BOM material control

Fire resistance
Class of reaction to Class A

LINEAR PERFORMANCE WARRANTY

25 Year Product Warranty
30 Year Linear Power Warranty




IEC 61215 , IEC 61730

WWW.HY-PV.COM

HY535-N108EDD

Hyper N54


Engineering Drawings



Tolerance

Length: ±2mm
Width: ±2mm
Height: ±1mm
Hole Pitch: ±2mm

I-V Curves



Electrical Characteristics

	HY515-N108EDD	HY520-N108EDD	HY525-N108EDD	HY530-N108EDD	HY535-N108EDD
Pmax(W)	515	520	525	530	535
Vmp(V)	33.93	34.13	34.32	34.51	34.70
Imp(A)	15.18	15.24	15.30	15.36	15.42
Voc (V)	40.95	41.25	41.55	41.85	42.15
Isc(A)	15.94	15.97	16.00	16.03	16.06
Module efficiency(%)	23.17	23.39	23.62	23.84	24.07
Maximum system voltage(V)			1500		
Fuse Rating(A)			30		
Temperature coefficient Pmax(%/°C)			-0.30		
Temperature coefficient Isc(%/°C)			0.046		
Temperature coefficient Voc(%/°C)			-0.25		

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

Bifacial Output-Backside Power Gain

10%	Pmax(W)	566.5	572	577.5	583	588.5
	Module efficiency(%)	25.49	25.73	25.98	26.23	26.48
20%	Pmax(W)	618	624	630	636	642
	Module efficiency(%)	27.80	28.07	28.34	28.61	28.88

Working Characteristics

	HY515-N108EDD	HY520-N108EDD	HY525-N108EDD	HY530-N108EDD	HY535-N108EDD
Pmax(W)	393	397	401	405	409
Vmp(V)	31.83	32.02	32.21	32.40	32.59
Imp(A)	12.35	12.40	12.45	12.50	12.55
Voc(V)	38.51	38.78	39.05	39.31	39.58
Isc(A)	12.86	12.89	12.91	12.94	12.97
Power tolerance(%)			0~+3		
NOCT(°C)			44±2		

NOCT: Conditions:Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Mechanical Characteristics

Number of cells	108 pcs
Size of cell (mm)	182*105
Type of cell	N type Mono
Thickness of glass (mm)	2.0
Type of frame	Anodized aluminum alloy
Junction box	IP68
Size of module (mm)	1960*1134*30
Weight (kg)	27
Cables/connectors	4mm², MC4 compatible
Length of Cable	Portrait: +300mm/ -300mm

Packing Configuration

Pieces per pallet	36
Size of packing (mm)	1980*1120*1250
Weight of packing (kg)	1005
Pieces per container	864
Size of container	40' HQ

Maximum Ratings

Operating Temperature(°C)	-40~85
Operating humidity(%)	5-85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s

Revised in Jan 2025 1st Edition
CAUTION: All rights reserved by Huayao PV.
Specifications included in this datasheet are subject to change without notice

+86 0519 8216 0017
213213
165 Huachuang Road, Jintan District, Changzhou, China
market@hy-pv.com
www.hy-pv.com